



Material Safety Data Sheet

ALBRITE PA-75

Date Prepared: 3/10/08

Supersedes Date: 3/30/05

1. PRODUCT AND COMPANY IDENTIFICATION

RHODIA INC.
RHODIA NOVECARE
CN7500
8 Cedar Brook Drive
Cranbury NJ 08512-7500

Emergency Phone Numbers:

FOR EMERGENCIES INVOLVING A SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT CONTACT: CHEMTREC (800-424-9300 within the United States or 703-527-3887 for international collect calls) or Rhodia CAERS (Communication and Emergency Response System) at 800-916-3232.

For Product Information:

(888) 776-7337

Chemical Name or Synonym:

PHOSPHORIC ACID, MONO AND DIPHENYL ESTERS

Molecular Formula:

$C_6H_7O_4P$ / $C_{12}H_{11}O_4P$

2. HAZARDS IDENTIFICATION

A. EMERGENCY OVERVIEW:

Physical Appearance and Odor:

pale yellow / liquid, characteristic odor.

Warning Statements:

DANGER! CORROSIVE TO EYES. CAUSES SKIN IRRITATION. CAUSES BURNS. FLAMMABLE LIQUID AND VAPOR.

B. POTENTIAL HEALTH EFFECTS:

Acute Eye:

Corrosive. Will cause corrosive effects (burns or irreversible damage) to the eyes. Causes redness, tearing, burns.

Acute Skin:

May cause significant irritation to the skin. May cause redness, inflammation, burns.

Acute Inhalation:

May cause significant respiratory tract irritation, coughing, a burning sensation, shortness of breath.

Acute Ingestion:

Low acute oral toxicity. May cause irritation, nausea, vomiting.

Chronic Effects:

This product does not contain any ingredient designated by IARC, NTP, ACGIH or OSHA as probable or suspected human carcinogens.

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Component | CAS Reg Number | OSHA Hazard | % WT/WT |
|--------------------------------------|----------------|-------------|-----------|
| PHOSPHORIC ACID, MONOPHENYL ESTER | 701-64-4 | Y | ~ 26 |
| BUTANOL | 71-36-3 | Y | ~ 25 |
| PHOSPHORIC ACID, DIPHENYL ESTER | 838-85-7 | Y | ~ 23 |
| MONOPHENYL MONOBUTYL PHOSPHORIC ACID | 46438-39-5 | Y | ~ 13 - 14 |
| MONOBUTYL PHOSPHATE | 1623-15-0 | N | ~ 4 - 5 |
| PHENOL | 108-95-2 | Y | ~ 2.5 - 4 |
| DIBUTYL PHOSPHATE | 107-66-4 | Y | ~ 2 - 3 |

4. FIRST AID MEASURES

FIRST AID MEASURES FOR ACCIDENTAL:

Eye Exposure:

Hold eyelids open and flush with a steady, gentle stream of water for at least 15 minutes. Seek immediate medical attention, preferably with an ophthalmologist. If the physician is not immediately available, eye irrigation should be continued for an additional 15 minutes. If it is necessary to transport the patient to a physician and the eye needs to be bandaged, use a dry sterile cloth pad and cover both eyes.

Skin Exposure:

Immediately wipe excess material off skin with a dry cloth; then wash skin with plenty of soap and water for at least 15 minutes. Seek medical attention. Remove contaminated clothing and shoes while washing. Clean contaminated clothing and shoes before re-use or discard if they cannot be thoroughly cleaned.

Inhalation:

If respiratory irritation or distress occurs remove victim to fresh air. Seek medical attention if respiratory irritation or distress continues.

Ingestion:

Wash out mouth with water and keep at rest. Seek immediate medical attention.

MEDICAL CONDITIONS POSSIBLY AGGRAVATED BY EXPOSURE:

Inhalation of product may aggravate existing chronic respiratory problems such as asthma, emphysema or bronchitis. Skin contact may aggravate existing skin disease.

NOTES TO PHYSICIAN:

All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

5. FIRE FIGHTING MEASURES

FIRE HAZARD DATA:

Flash Point:

53 C (127 F). Flammability Class: FLAMMABLE.

Method Used:

Setaflash Closed Cup

Flammability Limits (vol/vol%):

| | |
|---------------|---------------|
| Lower: | Upper: |
| 1.4 | 11.2 |

Extinguishing Media:

Recommended: foam, water fog, carbon dioxide, dry chemical.

Special Fire Fighting Procedures:

Firefighters should wear NIOSH/MSHA approved self-contained breathing apparatus and full protective clothing. Keep unnecessary people away, isolate hazard area and deny entry. Evacuate residents who are downwind of fire. Dike area to prevent runoff and contamination of water sources. Dispose of fire control water later. Persons who may have been exposed to contaminated smoke should be immediately examined by a physician and checked for symptoms of poisoning. The symptoms should not be mistaken for heat exhaustion or smoke inhalation. Cool containers exposed to fire with water fog.

Unusual Fire and Explosion Hazards:

Containers may explode (due to the build-up of pressure) when exposed to extreme heat. Product will burn under fire conditions.

Hazardous Decomposition Materials (Under Fire Conditions):

oxides of phosphorus

oxides of carbon

6. ACCIDENTAL RELEASE MEASURES

Evacuation Procedures and Safety:

Ventilate closed spaces before entering. Wear appropriate protective gear for the situation. See Personal Protection information in Section 8.

Containment of Spill:

Dike or retain dilution water or water from firefighting for later disposal. Collect and contain contaminated absorbent and dike material for disposal. Cover spill area with foam to reduce vapors.

Cleanup and Disposal of Spill:

Pump any free liquid into an appropriate closed container (see Section 7: Handling and Storage). Recover material, if possible. DO NOT RETURN MATERIAL TO ITS ORIGINAL CONTAINER. Absorb with an inert absorbent. Shovel up into an appropriate closed container (see Section 7: Handling and Storage). Use non-sparking tools. Clean up residual material by washing area with water. Collect washings for disposal. Decontaminate tools and equipment following cleanup. The material should be properly packaged and disposed of in compliance with applicable regulations.

Environmental and Regulatory Reporting:

Do not flush to drain. Runoff from fire control or dilution water may cause pollution. Prevent material from entering public sewer system or any waterways. Spills may be reportable to the National Response Center (800-424-8802) and to state and/or local agencies.

7. HANDLING AND STORAGE**Minimum/Maximum Storage Temperatures:**

Not Available

Handling:

Personnel handling this product should be thoroughly trained as to its hazards. Do not get on skin or in eyes. Avoid breathing vapors and mists. Use nonsparking tools and grounded/bonded equipment and containers when transferring.

**** HAZARD WARNING]**This product belongs to a chemical family that HAS BEEN TESTED in combination with Trimethylolpropane , Trimethylolpropane derived products or their corresponding Trimethylolpropane homologs for toxicity of the thermal decomposition products in the absence of flame. Products in this chemical family PRODUCED OBSERVABLE ADVERSE HEALTH EFFECTS in laboratory animals. There is a possibility that this thermal decomposition produces bicyclic phosphates and/or phosphites. Bicyclic phosphates and phosphites have acute neurotoxic properties and may cause convulsive seizures in laboratory test animals. Therefore, this product should not be used in conjunction with Trimethylolpropane or Trimethylolpropane derived products unless tested to determine their decomposition toxicity. Follow all precautionary measures outlined in this Material Safety Data Sheet and/or contact Rhodia Inc.

Storage:

Store in an area that is clean, cool, dry, well-ventilated, away from ignition sources, away from incompatible materials (see Section 10. Stability and Reactivity), Store in original container.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Introductory Remarks:**

These recommendations provide general guidance for handling this product. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. While developing safe handling procedures, do not overlook the need to clean equipment and piping systems for maintenance and repairs. Waste resulting from these procedures should be handled in accordance with Section 13: Disposal Considerations.

Assistance with selection, use and maintenance of worker protection equipment is generally available from equipment manufacturers.

Exposure Guidelines:

Exposure limits represent regulated or recommended worker breathing zone concentrations measured by validated sampling and analytical methods, meeting the regulatory requirements. The following limits apply to this material, where, if indicated, S=skin and C=ceiling limit:

BUTANOL

| | Notes | TWA | STEL |
|-------|-------|-------------|------|
| ACGIH | | 20 ppm | |
| OSHA | C,S | 150 mg/cu m | |
| OSHA | C,S | 50 ppm | |

PHENOL

| | Notes | TWA | STEL |
|-------|-------|------------|------|
| ACGIH | S | 5 ppm | |
| OSHA | S | 5 ppm | |
| OSHA | S | 19 mg/cu m | |

DIBUTYL PHOSPHATE

| | Notes | TWA | STEL |
|-------|-------|-----------|------------|
| ACGIH | | 1 ppm | 2 ppm |
| OSHA | | 1 ppm | 10 mg/cu m |
| OSHA | | 5 mg/cu m | 2 ppm |

Engineering Controls:

Where engineering controls are indicated by use conditions or a potential for excessive exposure exists, the following traditional exposure control techniques may be used to effectively minimize employee exposures: local exhaust ventilation at the point of generation.

Respiratory Protection:

When respirators are required, select NIOSH/MSHA approved equipment based on actual or potential airborne concentrations and in accordance with the appropriate regulatory standards and/or industrial recommendations.

Eye/Face Protection:

Eye and face protection requirements will vary dependent upon work environment conditions and material handling practices. Appropriate ANSI Z87 approved equipment should be selected for the particular use intended for this material.

Eye contact should be prevented through use of chemical safety glasses with side shields or splash proof goggles. An emergency eye wash must be readily accessible to the work area. Face contact should be prevented through use of a face shield.

Skin Protection:

Skin contact should be prevented through use of suitable protective clothing, gloves and footwear, selected with regard for use conditions and exposure potential. Consideration must be given both to durability as well as permeation resistance.

Work Practice Controls:

Personal hygiene is an important work practice exposure control measure and the following general measures should be taken when working with or handling this material:

- (1) Do not store, use, and/or consume foods, beverages, tobacco products, or cosmetics in areas where this material is stored.
- (2) Wash hands and face carefully before eating, drinking, using tobacco, applying cosmetics, or using the toilet.
- (3) Wash exposed skin promptly to remove accidental splashes or contact with this material.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical properties here represent typical properties of this product. Contact the business area using the Product Information phone number in Section 1 for its exact specifications.

Physical Appearance:

pale yellow / liquid.

Odor:

characteristic odor.

pH:
Not Applicable

Specific Gravity:
Not Available

Density:
1.11 to 1.15 g/ml at 20 C (68 F).

Water Solubility:
partially soluble

Melting Point Range:
Not Available

Boiling Point Range:
Not Available

Vapor Pressure:
Not Available

Vapor Density:
Not Available

Viscosity:
viscosity (centipoises) : 49 cps at 25 C (77 F).

10. STABILITY AND REACTIVITY

Chemical Stability:
This material is stable under normal handling and storage conditions described in Section 7.

Conditions To Be Avoided:
heat
See HAZARD WARNING under HANDLING : in Section 7.

Materials/Chemicals To Be Avoided:
strong oxidizing agents

Decomposition Temperature Range:
> 200 C (392 F)

The Following Hazardous Decomposition Products Might Be Expected:

Decomposition Type: thermal
oxides of phosphorus
oxides of carbon
Acids of phosphorus

Hazardous Polymerization Will Not Occur.

Avoid The Following To Inhibit Hazardous Polymerization:

not applicable

11. TOXICOLOGICAL INFORMATION

Acute Eye Irritation:

Toxicological Information and Interpretation:

eye - eye irritation, rabbit. Corrosive.

Acute Skin Irritation:

Toxicological Information and Interpretation:

skin - skin irritation, rabbit. May cause significant irritation to the skin.

Corrositex - In vitro-corrositex, **. Corrosive PGII.

Acute Dermal Toxicity:

Toxicological Information and Interpretation:

LD50 - lethal dose 50% of test species, > 2000 mg/kg, rat.

Acute Respiratory Irritation:

No test data found for product.

Acute Inhalation Toxicity:

No test data found for product.

Acute Oral Toxicity:

Toxicological Information and Interpretation:

LD50 - lethal dose 50% of test species, 2020 mg/kg, rat.

Chronic Toxicity:

This product does not contain any substances that are considered by OSHA, NTP, IARC or ACGIH to be "probable" or "suspected" human carcinogens.

Toxicological Information and Interpretation - MUTAGENICITY, **. Ames Test: Negative. - MUTAGENICITY, **. Mouse Lymphoma Negative.

12. ECOLOGICAL INFORMATION

Ecotoxicological Information:

No data found for product. May cause adverse environmental impact if material reaches waterways.

Chemical Fate Information:

No data found for product.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method:

Chemical additions, processing or otherwise altering this material may make the waste management information presented in this MSDS incomplete, inaccurate or otherwise inappropriate. Please be advised that state and local

requirements for waste disposal may be more restrictive or otherwise different from federal laws and regulations. Consult state and local regulations regarding the proper disposal of this material. Please contact technical service support at the phone number in section one of this MSDS to obtain suggestions for proper disposal of this product.

EPA Hazardous Waste - YES

EPA RCRA HAZARDOUS WASTE CODES:

"C" Corrosive.

14. TRANSPORT INFORMATION

Transportation Status: IMPORTANT! Statements below provide additional data on listed DOT classification.

The listed Transportation Classification does not address regulatory variations due to changes in package size, mode of shipment or other regulatory descriptors.

US DOT:

Hazard Class..... 8 (3)

Shipping Name:

CORROSIVE LIQUID, FLAMMABLE, N.O.S.

Technical Shipping Name:

BUTYL ALCOHOL/PHENYL ACID PHOSPHATE

ID Number..... UN2920

Packing Group.... II

Labels..... CORROSIVE, FLAMMABLE LIQUID

Emergency Guide #.... 132

TDG:

Hazard Class..... 8 (3)

Shipping Name: CORROSIVE LIQUIDS, FLAMMABLE, N.O.S.

Technical Shipping Name: BUTYL ALCOHOL/PHENYL ACID PHOSPHATE

ID Number..... UN2920

Packing Group.... II

IMO:

Hazard Class..... 8 (3)

Shipping Name: CORROSIVE LIQUID, FLAMMABLE, N.O.S.

Technical Shipping Name: BUTYL ALCOHOL/PHENYL ACID PHOSPHATE

ID Number..... UN2920

Packing Group.... II

IATA:

Hazard Class..... 8 (3)

Shipping Name: CORROSIVE LIQUID, FLAMMABLE, N.O.S.

Technical Shipping Name: BUTYL ALCOHOL/PHENYL ACID PHOSPHATE

ID Number..... UN2920

Packing Group.... II

15. REGULATORY INFORMATION

Inventory Status

| Inventory | Status |
|------------------------|---------------|
| UNITED STATES (TSCA) | Y |
| CANADA (DSL) | Y |
| EUROPE (EINECS/ELINCS) | N |
| AUSTRALIA (AICS) | Y |
| JAPAN (MITI) | Y |
| SOUTH KOREA (KECL) | Y |

Y = All ingredients are on the inventory.

E = All ingredients are on the inventory or exempt from listing.

P = One or more ingredients fall under the polymer exemption or are on the no longer polymer list. All other ingredients are on the inventory or exempt from listing.

N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing.

FEDERAL REGULATIONS

Inventory Issues:

All functional components of this product are listed on the TSCA Inventory.

SARA Title III Hazard Classes:

| | |
|-----------------------|-------|
| Fire Hazard | - YES |
| Reactive Hazard | - NO |
| Release of Pressure | - NO |
| Acute Health Hazard | - YES |
| Chronic Health Hazard | - NO |

SARA 313 Chemicals

BUTANOL (~25%) PHENOL (~2.5 - 4%)

SARA Extremely Hazardous Substances (EHS)/CERCLA Hazardous Substances

| Ingredient | CERCLA/SARA RQ | SARA EHS TPQ |
|-------------------|-----------------------|---------------------|
| BUTANOL | 5000 lbs | |
| PHENOL | 1000 lbs | 500 10000 |

STATE REGULATIONS:

This product does not contain any components that are regulated under California Proposition 65.

16. OTHER INFORMATION

National Fire Protection Association Hazard Ratings--NFPA(R):

- 3 Health Hazard Rating--Serious
- 2 Flammability Rating--Moderate
- 1 Instability Rating--Slight

National Paint & Coating Hazardous Materials Identification System--HMIS(R):

- 3 Health Hazard Rating--Serious
- 2 Flammability Rating--Moderate
- 1 Reactivity Rating--Slight

Reason for Revisions:

Change and/or addition made to Section 3, Warning Statements in Section 3, Section 9, Regulatory Review and

Update.

Key Legend Information:

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

TLV - Threshold Limit Value

PEL - Permissible Exposure Limit

TWA - Time Weighted Average

STEL - Short Term Exposure Limit

NTP - National Toxicology Program

IARC - International Agency for Research on Cancer

ND - Not determined

RHODIA - Rhodia Established Exposure Limits

Disclaimer:

The information herein is given in good faith but no warranty, expressed or implied, is made.

**** End of MSDS Document ****